



# Mobile scissor lift

## 230V 1200KG

### LT1200EA



- 1200kg lifting capacity
- Three-stage adjustable table top
- Mechanical locking
- Adjustable lifting pads
- Insulated table top

#### Technical specifications

Voltage	1200 kg
Lifting capacity	230 V - 1 Fase
Power	770 - 1400 mm
Platform dimensions	650 - 1830 mm
Protection class	650 - 1830 mm
Min. platform height (without pads/with pads)	650 - 1830 mm
Platform height max (without pads / with pads middle position / with pads high position)	650 - 1830 mm
Lifting pads (min / max)	650 - 1830 mm
Platform adjustable range	650 - 1830 mm



#### Features

- Table top with 104 M10 screw holes arranged in a 100 x 100 mm pattern, designed for easy attachment of tools and lifting adapters.
- The lift table is easily adjustable longitudinally and transversely and can be tilted 5 degrees
- Swivel castors including brake
- Folding bar for optimal working space
- Integrated, electro-hydraulic unit 230V
- Double hydraulic cylinder plus electromechanical lock for extra safety
- Includes 6 lifting pads with adjustable spindles
- Easy-to-operate control unit incl. magnetic holder for optimal positioning
- Insulated table top and lifting adapters for safe working on electric cars

Dimensions (mm)

